



# Linqing Kaige Bearing Co., Ltd.



2.559 Inch | 65 Millimeter x 4.724 Inch | 120 Millimeter x 0.906 Inch | 23 Millimeter SKF NU 213 ECP/C3 Cylindrical Roller Bearings

Bearing No. NU 213 ECP/C3

NU 213 ECP/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.065
EAN	7316577029485
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	65MM Bore; Straight Bore Profile; 120MM Outside Diameter; 23MM Width;



## Linqing Kaige Bearing Co., Ltd.

	Polymer Cage Material; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NU 213 ECP/C3
Weight / LBS	2.346
B	0.906 Inch   23 Millimeter
d	2.559 Inch   65 Millimeter
D	4.724 Inch   120 Millimeter
bore diameter:	65 mm
static load capacity:	118 kN
outside diameter:	120 mm
precision rating:	Not Rated
overall width:	23 mm
maximum rpm:	6700 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Polyamide
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	23 mm
operating temperature range:	Maximum of +300 ° F



## Linqing Kaige Bearing Co., Ltd.

fillet radius:	1.5 mm
dynamic load capacity:	122 kN
series:	NU2